

agroliner Three-axle turntable platform trailers

Type: PWO24 24 tonne permissible total weight

Standard equipment:

- Tyres:** 6 x 385/65 R22.5 factory refurbished tyres on centre well rims 80 km/h permitted
- Axles:** ADR tapered roller bearing axles, 3 x 11.3 tonnes axle load (105 km/h), 2050 mm track width without ABS up to 60 km/h, wheel brake 406 x 120 mm, 130 mm square axle
- Springs:** 2-layer parabolic spring suspension, 100 mm wide, approved for up to 105 km/h, overload protection on all 6 springs, rocker arms between the 2nd and 3rd axles,
- Steering:** Turntable steering with ball bearing turntable and type-tested triangular drawbar 1,990 mm, Height adjustable as well as drawbar relief
- Brake system:** dual line service brake system with automatic load-dependent brake force control (ALB), 2x 6 x diaphragm brake cylinder, spindle parking brake for the rear axle
- Chassis frame:** welded steel construction; double T main load bearer
- Plateau:** 4 mm steel floor, lashing points on the outer frame profile every 500 mm
- Electrical system:** 12 Volt system according to the guidelines of the StVZO (German traffic laws) with 7-pin connecting cable, triangular reflector and yellow side reflectors, 3 function rear lights (rubber mounted), number plate lights, position lights
- Accessories:** stable underride protection, number plate bracket, wheel chocks with bracket, plastic mudguard at the rear, park sockets for all connections on the drawbar
- Paintwork:** vehicle blasted with steel grit and also degreased, chip-resistant primer, sealing of areas in particular risk of corrosion using bodywork sealing compound, top coat in German quality dual-component gloss paint.
- Colouring:** Kröger green
- Technical data:**
- | | |
|---------------------------|---|
| permissible total weight: | 24,000 kg |
| Empty weight: | approx. 4,850 kg (in the basic equipment) |
| Payload: | approx. 19,150 kg |
- Dimensions:**
- | | |
|-----------------------|-----------------------------|
| Total vehicle length: | approx. 11,670 mm (overall) |
| Total vehicle width: | approx. 2,470 mm (outside) |
| Load length: | approx. 9,850 mm |
| Catwalk height: | approx. 1,300 mm |

(Technical changes reserved)

- F 915P1 Rubber buffer mounted on the rear axle
- F 916P Plastic wall-protective profile below the side board walls (in conjunction with A 170P or A 250P)

R WHEELS

- R 200P1 Tyres, "new" 385/65R22.5 (105 km/h) manufacturer PIRELLI Triathlon (EU Tyre Label B,A,70)
- R 220P1 Tyres, "new" 425/65R22.5 (105 km/h) manufacturer Continental (catwalk height approx. + 40 mm)
- R 240P1 Tyres, "new" 445/65R22.5 (105 km/h) manufacturer Continental (catwalk height approx. + 50 mm)
- R 243P1 Tyres, "new" 500/60R22.5 NOKIAN Country King (40 km/h), catwalk height approx. + 100 mm), rims with imprint depth + 30 mm, i.e. track is narrower
- R 245P1 Tyres, "new" 560/45R22.5 BKT FLOTATION RADIAL, profile FL 693 M, (70 km/h), rims with imprint depth ID + 30 mm, i.e. track becomes narrower
- R 246P1 Tyres, "new" 560/60R22.5 BKT FLOTATION RADIAL, profiles FL 693 M, (70 km/h), (catwalk height approx. + 100 mm), rims with imprint depth ID + 30 mm, i.e. track becomes narrower
- R 259P1 Tyres "new" 560/60R22.5 NOKIAN Country King (65 km/h) 161D with reinforced rims 20.00 (tyre load at 1.5 bar 10 km/h = 5,000 kg) (catwalk height approx. + 100 mm)

L PAINTWORK

- L 145P Special paintwork, chassis and superstructure according to RAL tone
- L 150P Stone chipping protection coating under the superstructure in the area above the wheels

T EXPERT'S REPORT/HANDING OVER

- T 150P Expert's report for 40 km/h registration
- T 200P Expert's report for 60 km/h registration
- T 300P Expert's report for 105 km/h registration (only in conjunction with F400P, F510P, F520P, F655P, R 2004 or R 2204, or R 2404 / total external width may not exceed 2550 mm)
- T 420P Dekra load-securing certificate
- T 9004 Transport costs, German post code 0-4
- T 9014 Transport costs, low-bed transport, postal code 0-4 (when ordering configuration A 360P)
- T 9104 Transport costs, German post code 5-9
- T 9114 Transport costs, low-bed transport, postal code 5-9 (when ordering configuration A 360P)

All prices indicated are subject to legal VAT.

Version: October 2019
